


Digital Advantages



The IC-F29DR is available with 16 digital channels and utilises 6.25 kHz narrow channel spacing. Even in urban areas where analogue PMR446 users often experience channel congestion, digital channels offer less interference. Therefore, it is so suitable for professional use.

Pan-European Licence-Free Communication



The IC-F29DR meets pan-European digital and analogue licence-free standards. The IC-F29DR is ideal for organisations and businesses where the workplace is constantly changing such as construction sites and events.

Options

Headsets



HS-94LWP
Earhook headset with boom microphone for hands-free operation



HS-95LWP
Behind-the-head type with boom microphone for hands-free operation



HM-153LA
Lapel type microphone with earphone



HM-166LA
Light weight earphone microphone

Speaker-microphones



HM-168LWP
IP67 waterproof speaker-microphone



HM-158LA
Compact size speaker-microphone



HM-159LA
Full size durable speaker-microphone



HS-97 + VS-4LA or OPC-2004LA*
Throat microphone with earphone

* Either VS-4LA or OPC-2004LA is required when using HS-97 headset.
VS-4LA: PTT switch cable for manual PTT operation
OPC-2004LA: Plug adapter cable for VOX hands-free operation
HS-94 and HS-95 also can be used with either VS-4LA or OPC-2004LA.

Throat microphone

Battery packs



BP-278



BP-279



BP-280

Battery packs	Type	Capacity	Operating time*
BP-278	Rechargeable Li-ion 7.2 V	1130 mAh (min.) 1190 mAh (typ.)	12 hours (Approx.)
BP-279	Rechargeable Li-ion 7.2 V	1485 mAh (min.) 1570 mAh (typ.)	17 hours (Approx.)
BP-280	Rechargeable Li-ion 7.2 V	2280 mAh (min.) 2400 mAh (typ.)	26 hours (Approx.)

* Tx: Rx: standby = 5 : 5 : 90 duty cycle. Power save ON.

Multi-charger



BC-214

Rapidly charges up to six transceivers and/or battery packs at the same time*.

* AD-130 charger adapter is supplied with BC-214.

Charger bracket



MB-130

For use with BC-213.

Power supply cable

OPC-656
For use with BC-214.

Cigarette lighter cable

CP-23L
For use with BC-213.

Programming software

CS-F29DR
Allows quick and simple setting from a PC.

Programming cable

OPC-478UC: USB cable

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. dPMR and the dPMR logo are trademarks of the dPMR MoU Association. AMBE+2 is a trademark and property of Digital Voice Systems, Inc.

Icom Inc. www.icom.co.jp/world

Count on us!

Icom (Europe) GmbH

Communication Equipment
Auf der Krautweide 24, 65812 Bad Soden am Taunus, Germany
Phone : +49 (6196) 76685-0 E-mail : info@icom-europe.com
Fax : +49 (6196) 76685-50 URL : <http://www.icomeurope.com>

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer" Bajos A 08174,
Sant Cugat del Valles, Barcelona, Spain
Phone : +34 (93) 590 26 70 E-mail : icom@icomspain.com
Fax : +34 (93) 589 04 46 URL : <http://www.icomspain.com>

Icom (UK) Ltd.

Blacksole House, Alitra Park, Herne Bay, Kent, CT6 6GZ, U.K.
Phone : +44 (0) 1227 741741 E-mail : info@icomuk.co.uk
Fax : +44 (0) 1227 741742 URL : <http://www.icomuk.co.uk>

Icom France s.a.s.

Zac de la Plaine, 1 Rue Brindejenc des Moulinais, BP 45804, 31505 Toulouse Cedex 5, France
Phone : +33 (5) 61 36 03 03 E-mail : icom@icom-france.com
Fax : +33 (5) 61 36 03 00 URL : <http://www.icom-france.com>

Your local distributor/dealer:

ICOM

Digital Licence-Free Comms with Professional Level Durability



dPMR™
igital

Rugged
MIL-STD 810

IP67

**dPMR™ 446/PMR446 TRANSCEIVER
IC-F29DR**

ACTUAL SIZE



dPMR™ 446/PMR446 TRANSCEIVER
IC-F29DR



Events



Construction sites



Security

Compact Waterproof Digital Transceiver **for Professional Users**



Digital and Analogue Dual Mode

The IC-F29DR can be used in both digital and analogue mode at the same time and can scan both zones at once. This allows an organisation to operate both digital and analogue radios in their fleets.



IP67 Waterproof and Dust-tight

The IC-F29DR can withstand 1 m depth of water for 30 minutes. This rugged construction provides dust-tight protection making it suitable for outdoor use.



Outstanding Audio Quality

800 mW audio output is provided from the large 36 mm speaker. The IC-F29DR can deliver loud and intelligible audio even in noisy environments.



Group Call Communication

Similar to analogue CTCSS and DTCS codes, the digital Common ID also can be used for a group call. These codes and ID can be programmed to the 16 position rotary selector for instant call capability.



VOX for Hands-free Operation

With either optional headset* HS-94LWP or HS-95LWP, built-in VOX function provides convenient hands-free operation.* HS-94 and HS-95 also can be used with OPC-2004LA.



Voice Announcement Function

When you rotate the rotary selector, the radio announces the selected channel number. The radio also announces the zone number and mode when the zone button is pushed.



12 types of Ring Tone

The Call-Ring function allows you to call your group members with 12 types of ring tone. When you pre-arrange any ring tone for an emergency, the ring tone can be used for an emergency alert.



Other Features

·26 hours operating time ·Channel Set Mode ·Power ON scan ·Tone scan (analogue) ·Nuisance delete ·Answer back call (analogue) ·LED light indicator ·Status Call (RX only) ·PC programmable ·AMBE+2™ dPMR standard vocoder

Specifications

- Usable channels: 8 ch (PMR 446) 16 ch (dPMR™ 446)
- Output power: 500 mW (ERP)
- Audio output power: Internal speaker 800 mW typical (with 12 Ω load) (at 5% distortion) External speaker 400 mW typical (with 8 Ω load)
- Dimensions : 52.2 (W) × 186.1 (H) × 30.3 (D) mm (with BP-280)
- Weight: 270 g (with MB-133, BP-280)
- Communication range*: Approximately 11km (Wide open space)
- Operating temperature: -25°C to +55°C
- IP rating: IP67 (Dust-tight and waterproof protection)
- Military standard: MIL-STD-810-G

* Communication range may differ depending on operating environment or weather conditions, etc. All stated specifications are subject to change without notice or obligation.

Supplied Accessories

(* May differ depending on version)



AC adapter
BC-123SE/SUK*



Rapid charger
BC-213



Battery pack
BP-280



Belt clip
MB-133